



PRODUCT DESCRIPTION

The double branch is used in the system for branching various sections of the ducting, with the purpose of achieving an smoke exhaust or a supply flow as homogenous as possible.

The standard version has the following parameters: radius $R1 = R2 = 150$ and $\alpha1 = \alpha2 = 90^\circ$. Supplied with strong joining profile DW30 at all ends.

The product is tested in accordance to EN 1366-9 and fulfils all the prescribed requirements of performance according to EN 12101-7, used in a rectangular smoke control system (see declaration of performance). The CE marked product complies with the essential requirements of the relevant European health, safety and environmental protection legislation.

ORDERING

	RRBD	700	300	400	150	90	90	150	150
Article code	RRBD	700	300	400	150	90	90	150	150
Side A (mm)	700	300	400	150	90	90	150	150	
Side B (mm)	300	300	400	150	90	90	150	150	
Side C (mm)	300	400	400	150	90	90	150	150	
Side D (mm)	300	400	150	150	90	90	150	150	
Angle $\alpha1$	90	90	90	90	90	90	90	90	
Angle $\alpha2$	90	90	90	90	90	90	90	90	
Radius R1 (mm)	150	150	150	150	150	150	150	150	
Radius R2 (mm)	150	150	150	150	150	150	150	150	

